

Aquamax ECO



- Energy-efficient motor with innovative electric control for optimisation of the efficiency level, saves up to 40% energy
- An additional 20% saving in energy is possible thanks to the newly developed Seasonal Flow Control (for Aquamax ECO 12000/16000)
- Flow-optimised impeller guarantees maximum hydraulic pump performance and improved displacement of coarse debris
- Large surface filter housing allows debris such as vegetation or koi waste up to 10 mm in size to pass through
- Second mechanically adjustable inlet for connection of skimmer/satellite filter for skimming surfaces or pond water
- Fully capable of withstanding winter conditions thanks to intelligent frost protection technology
- Suitable for use in swimponds and bathing ponds

CODE	OAMX40E	OAMX60E	OAMX80E	OAMX120E	OAMX160E
DESCRIPTION	Aquamax 4000 ECO	Aquamax 6000 ECO	Aquamax 8000 ECO	Aquamax 12000 ECO	Aquamax 16000 ECO
DIMENSIONS LXBXH	350x284x163mm				
POWER CONSUMPTION	50 Watt	60 Watt	80 Watt	130 Watt	170 Watt
VOLTAGE	220-240V/50Hz				
MAX FLOW	4000L/H	6000L/H	8000L/H	12000L/H	16000L/H
MAX HEAD	3.2M	3.6M	4.0M	5.2M	5.6M



H (mWS)

