







Bitron C



All Bitron C UVC clarifiers have an automatic cleaning function. Supplied with flow nozzle that optimises flow through the cleaning rotor at low pump performance. Cable length 5 m. OASE provides a full guarantee of 2 years (except bulbs) on all UVC clarifiers. All devices have the electrical protection class 1 rating.

-  Automatic self-cleaning
-  Individually adjustable flow control
-  Clear water through flocculation of algae
-  High-quality workmanship in impact-resistant plastic
-  Simple installation thanks to an extensive range of connection accessories
-  Safely and effectively removes bacteria and germs (through UVC radiation)



CODE	OUV18	OUV24	OUV36	OUV55	OUV72	OUV110
DESCRIPTION	Bitron UV 18C	Bitron UV 24C	Bitron UV 36C	Bitron UV 55C	Bitron UV 72C	Bitron UV 110C
DIMENSIONS LxBxH	440x180x198mm		600x180x198mm		731x216x201mm	
VOLTAGE	220-240V/50-60Hz					
INLET	1½"		2"			
OUTLET x2	1½"					
FUNCTION CHECK	Control Window					
MAX OPERATING PRESSURE	0.5 bar				1 bar	
MAX PUMP CAPACITY	15000l/hr		30000l/hr		40000l/hr	
POWER CONSUMPTION	18W	24W	36W	55W	72W	110W
FLOW THROUGH, WITHOUT BYPASS	2200l/hr	3500l/hr	4500l/hr	6500l/hr	9000l/hr	12000l/hr