



KOK SERIES FILTRATION COMBO

FEATURES

- Bobbin wound fiberglass filter tank
- Easy-to-use 6-way multi-port valve and water drain plug
- Transparent lid cover allows easy inspection of filtration bed
- Diffuser with curved fan ensures better distribution of water over the media bed
- The PE granule filter media creates an enormous filter surface that filters both small particle and bacteria from the water
- Air release valve enables easy release of trapped air during operation of the filter
- Equips with Emaux pump to generate water flows
- Equips with Emaux Air blower to allow an efficient and effective air scouring
- Applicable for most of Fish Pond & Aquarium filtration system
- PE Granule filtration media included

FUNCTIONS: Refer to 6-Way Multi-port Valve

- Maximum Working Pressure 250kPa/36psi/2.5bar
- Factory Testing Pressure 400kPa/58psi/4.0bar
- Media Type Recommended Polyethylene granule
- Maximum Filtration Velocity 50m³/h/m²
- Maximum Water Temperature 43°C(109°F)

TECHNICAL CHARACTERISTICS

| Code | Model | Filter | Pump | Air Blower | Max.Flow Rate |
|----------|--------|--------|-------|------------|------------------------------|
| 88033225 | KOK-65 | S650R | SC150 | AB550 | 400lpm 24.0m ³ /h |
| 88033331 | KOK-80 | S800R | SB20 | AB550 | 583lpm 35.0m ³ /h |
| 88033432 | KOK-90 | S900R | SB30 | AB550 | 666lpm 40.0m ³ /h |

