

Aquaskim



- 🌊 Thanks to a two-piece telescopic tube it is infinitely height adjustable
- 🌊 A float automatically handles water level differences, the height can be easily adjusted without tools. Even adapting to shallow water levels is possible
- 🌊 A smaller tube diameter ensures less air content and thus prevents the surface skimmer from floating
- 🌊 Just 10kg ballast material in the skimmer's base will ensure absolutely stable set-up



| | |
|------------------------|----------------|
| CODE | OPS350 |
| DESCRIPTION | Aquaskim 40 |
| HEIGHT ADJUSTABILITY 1 | 550—830mm |
| HEIGHT ADJUSTABILITY 2 | 300—550mm |
| TUBE DIAMETER | 80mm |
| FILTER BASKET VOLUME | 1.4L |
| PUMP CAPACITY | 4000-16000l/hr |
| OUTLET CONNECTION | 1½" |

Pondovac 3



- 🌊 PONDovac 3 enables continuous, powerful vacuum removal of dirt and sludge from the pond. Two same-size cylinders are filled and emptied in alternating cycles.
- 🌊 Transport castors ensure that the device can be easily moved
- 🌊 Accessories include: String algae nozzle, floor nozzle, suction tube extension, folding transport handle, debris collection bag for the water return
- 🌊 It is also ideally suited for wet vacuum implementation in the household

| CODE | DESCRIPTION | DIMENSIONS | LENGTH SUCTION HOSE | LENGTH DISCHARGE HOSE | CABLE LENGTH |
|------|-------------|------------|---------------------|-----------------------|--------------|
| OPV3 | Pondovac 3 | 380x685mm | 5m | 2.5m | 4m |